



Peerless Pump

HORIZONTAL SPLIT CASE PUMP

Series BT

<p>Specifications:</p>	<p>The Peerless® BT Pump</p>
<p>Rates of Flow Up to 7,500 gpm (1,704 m³/hr)</p>	<p>The Peerless BT pump is a cast iron, bronze-fitted single stage double suction horizontal split case pump. Engineered and manufactured in the U.S.A. using the latest technology, the BT has been specifically designed to meet the needs of both installing contractors and owners in the HVAC and Plumbing Systems for commercial buildings.</p>
<p>Pump Sizes 2" through 10" discharge</p>	<p>The BT pump is a cost-effective, reliable, durable and efficient pump: the best value in the marketplace.</p>
<p>Head Up to 250 feet (76m)</p>	<p>Featuring Innovative compact casing design allows for space savings in pump room layouts. Its true axially-split case design allows for removal of the rotating element without disturbing piping or motor.</p>
<p>Working Pressure 175 psig (12 kg/cm², 1,207kPa)</p>	<p>Cast bronze, one piece impeller is hydraulically and dynamically balanced for vibration-free performance and longer bearing and mechanical seal life. Keyed to the shaft, the impeller is positioned axially with stainless steel retaining rings for easy, accurate re-assembly and centering in casing.</p>
<p>Horsepower Up to 250 hp (186 kW)</p>	<p>Mechanical seals, standard on all pumps, are capable of handling ethylene glycol solutions necessary for chilled water applications and are suitable for temperatures up to 225°F for hot water applications. Mechanical seals also eliminate expensive stuffing box leakage. The gland is furnished in series 300 stainless steel to resist corrosion.</p>
<p>Temperature Up to 225°F (107°C)</p>	<p>Shaft is solid 416 stainless steel for superior corrosion resistance and can accommodate both right hand and left hand rotation allowing for field change of rotation if required.</p>
<p>Materials of Construction Cast iron; bronze fitted</p>	<p>Bearings meet or exceed L₁₀ life of 20,000 hours under maximum loading conditions (average life 100,000 hours).</p>
	<p>Durable and Maintainable Pump owners and users will appreciate the BT pump's durability and ease of maintenance. Grooved impeller skirts in combination with bronze casing rings extend the life of this critical clearance, thus increasing meantime between preventive maintenance (MTBPM). Precision machining of the casing and drop-in, self-aligning cartridge bearings provide accurate and quick installation of the rotating assembly during maintenance. Bearings can be replaced without disassembling the pump. Parts are made in the U.S.A. and readily available when required.</p>



